



RECOVERMATE AVAILABLE IN 1/2" (13 mm) THICKNESS ONLY. DURAPINK AVAILABLE IN 1/2" (13 mm), 3/4" (19 mm) and 1" (25 mm) THICKNESSES.

8 FASTENERS PER 4' X 8' (1200 mm x 2400 mm)  
<sup>2</sup>  
 FASTENING PATTERN, 1 FASTENER EVERY 4 SQUARE FEET (3720 cm<sup>2</sup>).

NOTES:

1. FOR CRITERIA ON INSULATION FASTENERS AND PLATES, SEE SPECIFICATIONS.
2. SEAM FASTENING PLATES MAY BE USED IN LIEU OF INSULATION FASTENING PLATES FOR INSULATION ATTACHMENT ON THIS SYSTEM ONLY.
3. DURAPINK INSULATION CAN ONLY BE USED ON RECOVERY PROJECTS AS A SINGLE LAYER DIRECTLY OVER EXISTING ROOFING MEMBRANE. OVER EXISTING PVC MEMBRANES, A LAYER OF HP PROTECTIVE MAT MUST BE USED AS A SEPARATOR. REFER TO SPECIFICATION FOR ADDITIONAL REQUIREMENTS.

WFMA-27.3  
 FOAMULAR, DURAPINK OR  
 DOW RECOVERMATE ATTACHMENT