



NOTES:

1. WHEN SPECIFIED, VERSIGARD/VERSIGARD WHITE EPDM, VERSIWELD TPO, VERSIFLEX PVC, AND VERSIFLEECE TPO MEMBRANE MAY BE ADHERED DIRECT WITH APPLICABLE ADHESIVE, REFER TO WEATHERBOND SPECIFICATIONS.
2. APPLY EPDM PRIMER TO THE METAL FLANGE AND MEMBRANE SURFACE PRIOR TO INSTALLING QUICK APPLIED UNCURED EPDM FLASHING.
3. AS AN OPTION TO THERMOPLASTIC NON-REINFORCED MEMBRANE FLASHING, PRE-FABRICATED SPLIT PIPE SEAL MAY BE USED.

DIMENSIONS	mm	
(A)	3"	76 MIN.
(B)	2"	51 MIN.
(C)	1/2"	13 MIN.

FREQUENCY OF VENTS		
TYPE OF SUBSTRATE	NO. OF VENTS	MAX. AREA PER VENT
CELLULAR OR PERLITE LIGHTWEIGHT INSULATING CONCRETE	1	2,000 S.F. (186M <sup>2</sup> )



ONE-WAY PRESSURE RELIEF VENT

— MEMBRANE  
 APPROVED SUBSTRATE  
0 — SEE NOTE(S)

SPEC. SUPPLEMENT

G-04.2