


TPO ONLY  
(NOT FOR PVC)

NOTES:

1. FASCIA DECK FLANGE MUST BE TOTALLY COVERED BY TPO PEEL & STICK COVER STRIP WITH MINIMUM 2" (5cm) COVERAGE PAST NAIL HEADS.
2. REFER TO [MR Z1.1](#) & [MR Z1.2](#) AT THE END OF THIS SECTION.
3. THIS DETAIL IS NOT RECOMMENDED FOR ROOFS THAT ARE LIKELY TO EXPERIENCE SIGNIFICANT SNOW AND ICE UP-SLOPE FROM GUTTER/EDGE WITH A PITCH OF 3:12 OR GREATER. REFER TO DETAILS: [MRT1.1A](#), [MR T1.3](#), [MR T1.4](#), [MR T1.6](#).

**A** 1-1/2" (38mm) RING SHANK NAILS @ 6" (15cm) O.C. MAXIMUM

**B** HPW FASTENERS @ 12" (30cm) O.C. OR RING-SHANK NAILS @ 4" (10cm) O.C. & STAGGERED 3/4" (2cm) O.C.



GUTTER WITH AND WITHOUT FASCIA

	• HIGH DENSITY RECOVER BOARD
	• IN-FILL INSULATION
<b>A</b> <b>0</b>	• SEE NOTE(S)

METAL RETROFIT  
MR | T1.5