

WeatherBond TPO Fire-Rated Fleece Roofing System
April 23, 2018

WeatherBond is pleased to introduce its TPO Fire-Rated (FR) Fleece roofing system. This system uses WeatherBond's patent-pending optimized fleece to provide a UL Class A fire rating for direct application to wood decks. The TPO FR Fleece system is approved for mechanically attached applications and eliminates the need for multiple layers of base sheets or gypsum thermal barriers. The TPO FR Fleece system offers a variety of features and benefits, including:

- Labor savings of up to 25%
- No application temperature restrictions
- No VOCs or odors
- Greater puncture resistance than modified bitumen
- 67% fewer seams than modified bitumen
- Excellent resistance to hail and punctures
- 115-mil membrane thickness adds toughness and durability
- UL Class A approval for direct application to combustible decks

NOTE: Fleece FR TPO membranes are only approved for mechanically attached applications and are not approved for fully adhered applications.

Fleece FR TPO Membrane				
Product Code	Description	Size	Weight	Stocking Location
330794	WHITE FLEECE FR TPO-115-mil	10' x 50'	203 lbs	Tooele, UT
330205	WHITE FLEECE FR TPO-115-mil	10' x 100'	390 lbs	Tooele, UT

If you have any questions, or for more information, please contact your Independent Sales Representative.

Sincerely,



Austin Kulp
Fleece Product Manager

WEATHERBOND
ROOFING SYSTEMS

P.O. Box 251 | Plainfield, PA 17081 | 866.471.5125 | FAX: 717.960.4034 | www.weatherbondroofing.com

Single-Ply Simplified