

#### Material Name: LiquiSeal Metal Primer (B)

Product #: 330890B

### Section 1 - PRODUCT AND COMPANY IDENTIFICATION

Material Name LiquiSeal Metal Primer **Synonyms** Interior and Exterior Waterproofing **Chemical Family** Isocyanate **Product Use** Interior and exterior waterproofing. **Restrictions on Use** 

For industrial use only. **Manufacturer Information** Weatherbond P.O. Box 215 Plainfield, PA 17081 USA Phone: +1-866-471-5125 Emergency Phone #: +1-800-424-9300 (Chemtrec)

# Section 2 - HAZARDS IDENTIFICATION

### Classification in accordance with paragraph (d) of 29 CFR 1910.1200.





Resp. Sens. 1

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

GHS07

Acute Tox. 4	H332 Harmful if inhaled.
Skin Irrit. 2	H315 Causes skin irritation.
Skin Sens. 1	H317 May cause an allergic skin reaction.
STOT ST 3	H335 May cause respiratory irritation.
Eye Irrit. 2B	H320 Causes eye irritation.

GHS08 Health hazard



#### Material Name: LiquiSeal Metal Primer (B)

#### **Additional information:**

At temperatures up to 77°F (25°C), this product does not emit sufficient vapors to pose a respiratory hazard when used as directed. Above this temperature, concentrations may become hazardous in enclosed spaces. Ventilation using open windows, fans, or other means of creating airflow are typically sufficient engineering controls to maintain adequate ventilation at working temperatures.

#### Label Elements GHS Label Elements

This product is classified and labeled according to the Globally Harmonized System (GHS).

Signal Word Danger

#### Hazard-determining Components of Labeling

diphenylmethanediisocyanate, isomeres and homologues 4,4'-methylenediphenyl diisocyanate o-(p-isocyanatobenzyl)phenyl isocyanate

#### Hazard Statement(s)

Harmful if inhaled. Causes skin and eye irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reation. May cause respiratory irritation.

#### **Precautionary Statement(s)**

In case of inadequate ventilation wear respiratory protection. Avoid breathing dust/fume/gas/mist/vapours/spray. Wear protective gloves/protective clothing/eye protection/face protection. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing should not be allowed out of the workplace. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Specific treatment (see on this label). IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If skin irritation occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. IF ON SKIN: Wash with plenty of soap and water. IF INHALED: Call a POISON CENTER/doctor if you feel unwell. If experiencing respiratory symptoms: Call a POISON CENTER/doctor. Take off contaminated clothing and wash it before reuse. Store in a well-ventilated place. Keep container tightly closed. Dispose of contents/container in accordance with local/regional/national/international regulations.

#### WHMIS-symbols:



#### Material Name: LiquiSeal Metal Primer (B)

Product #: 330890B

D2A - Very toxic material causing other toxic effects



#### NFPA ratings (scale 0 - 4):

Health = 2 2 1 Fire = 1Reactivity = 1

# Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

### **Chemical characterization: Mixtures**

**Description:** Mixture of the substances listed below with nonhazardous additions.

Dangerous Components		
9016-87-9	diphenylmethanediisocyanate, isomeres and homologues	30-60%
101-68-8	4,4'-methylenediphenyl diisocyanate	30-60%
5873-54-1	o-(p-isocyanatobenzyl)phenyl isocyanate	10-13%

Additional Information: Exact concentrations are being withheld as trade secrets.

### Section 4 - FIRST AID MEASURES

#### **General information:**

Symptoms of poisoning may even occur after several hours.

#### **After Inhalation:**

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison center or doctor if you feel unwell or are experiencing respiratory symptoms.

#### After Skin Contact:

Wash with plenty of soap and water. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention.

#### **After Eye Contact:**



#### Material Name: LiquiSeal Metal Primer (B)

Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing. If eye irritation persists get medical advice/attention.

#### **After Swallowing:**

If swallowed, do not induce vomiting. Get medical attention right away.

#### Most Important Symptoms and Effects, both Acute and Delayed:

No further relevant information available.

#### Indication of any Immediate Medical Attention and Special Treatment needed:

No further relevant information available.

# Section 5 - FIRE FIGHTING MEASURES

#### **Suitable Extinguishing Agents:**

Use fire fighting measures that suit the environment.

#### **Special Hazards Arising from the Substance or Mixture:**

No further relevant information available.

#### **Protective Equipment:**

Mouth respiratory protective device.

### Section 6 - ACCIDENTAL RELEASE MEASURES

### Personal Precautions, Protective Equipment and Emergency Procedures:

See below:

#### **Environmental Precautions:**

Do not allow to enter sewers/ surface or ground water.

#### Methods and Materials for Containment and Cleaning Up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.

#### **Reference to other sections:**

See Section 7 for information on safe handling. See Section 8 for information on personal protective equipment. See Section 13 for disposal information.



#### Material Name: LiquiSeal Metal Primer (B)

Product #: 330890B

### Section 7 - HANDLING AND STORAGE

#### **Precautions for Safe Handling**

Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.

**Information about protection against explosions and fires:** No special measures required.

Storage

**Requirements to be met by storerooms and receptacles:** No special requirements.

**Information about storage in one common storage facility:** Not required.

**Further Information about Storage Conditions:** Keep receptacle tightly sealed.

**Special End Use(s):** No further relevant information available.

# Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

#### Additional information about design of technical systems: No further data; see item 7.

#### Component with limit values that require monitoring at the workplace:

#### 101-68-8 4,4'-methylenediphenyl diisocyanate

EL Long-term value: 0.005 ppm Ceiling limit value: 0.01 ppm Skin; S EV Long-term value: 0.005ppm Ceiling limit value: 0.02 ppm

#### **Additional Information:**

The lists that were valid during the creation were used as basis.

Personal Protective Equipment

#### **General Protective and Hygienic Measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.



### Material Name: LiquiSeal Metal Primer (B)

**Breathing Equipment:** 

Use suitable respiratory proctective device in case of insufficient ventilation.

### **Protection of Hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

#### Material of Gloves: Butyl rubber, BR

Fluorocarbon rubber (Viton) Nitrile rubber, NBR Natural rubber, NR

### **Eye Protection**



Tightly sealed goggles.

# Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

Form	Fluid	Color	According to product specification.
Odor	Characteristic	Odour threshold	Not determined
pH-value	Not determined	Change in condition Melting point/Melting range Boiling point/Boiling range	Undetermined > 350°C
Flash Point	> 200°C	Flammability (solid,gaseous)	Not applicable
Ignition temperature	400°C	Decomposition temperature	Not determined
Auto igniting	Product is not selfigniting	Danger of explosion	Product does not present an explosion hazard
Explosion limits Lower: Upper:	0.4 Vol % Not determined.	Vapor pressure	Not determined
Denisty at 20°C Relative density	1.24 g/cm3 Not determined	Solubility in / Miscibility with Water	-



#### Material Name: LiquiSeal Metal Primer (B)

#### Product #: 330890B

Vapour density Evaporation rate	Not determined Not determined	Not miscible or difficult to mix.
Partition coefficient (n-octanol/water)	Not determined	
Solvent content Organic solvents Other information	0.0% No further relevant information available	».

# Section 10 - STABILITY AND REACTIVITY

#### Thermal Decomposition/Conditions to be Avoided:

No decomposition if used according to specifications.

#### **Possibility of Hazardous Reactions**

No dangerous reactions known.

#### Conditions to Avoid

No further relevant information available.

#### **Incompatible Materials**

No further relevant information available.

#### Hazardous decomposition products

No dangerous decomposition products known.

# Section 11 - TOXICOLOGICAL INFORMATION

#### **Information on Toxicological Effects:**

Acute Toxicity		
LD/LC50 values that are relevant for classification:		
101-68-8 4,4'-methylenediphenyl diisocyanate		
Oral	LD50	2200 mg/kg (mouse)

#### Specific Symptoms in Biological Assay:

No further relevant information available.

#### **Primary Irritant Effect:**

**On the skin:** Irritant to skin and mucous membranes. **On the eye:** Irritating effect. **Sensitization**: Sensitizing possible through inhalation. Sensitization possible through skin contact.



#### Material Name: LiquiSeal Metal Primer (B)

Additional Toxicological Information:

The product shows the following dangers according to internally approved calculation methods for preparations: Harmful Irritant

#### **Carcinogenic Categories**

IARC (International Agency for Research on Cancer)		
9016-87-9	diphenylmethanediisocyanate, isomeres and homologues	3
101-68-8	4,4'-methylenediphenyl diisocyanate	3
NTP (National Toxicology Program)		
None of the ingredients is listed.		
OSHA-Ca (Occupational Safety & Health Administration)		
None of the ingredients is listed.		

# Section 12 - ECOLOGICAL INFORMATION

#### **Aquatic Toxicity:**

No further relevant information available.

#### Persistence and Degradability:

No further relevant information available.

#### **Bioaccumulative Potential:**

No further relevant information available.

#### Mobility in Soil:

No further relevant information available.

#### **Additional Ecological Information**

#### General Notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water. Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

#### **Other Adverse Effects:**

No further relevant information available.

### Section 13 - DISPOSAL CONSIDERATIONS

#### Waste Treatment Methods Recommendation:

Must not be disposed of together with household garbage. Do not allow product ot reach sewage system.



#### Material Name: LiquiSeal Metal Primer (B)

Product #: 330890B

#### **Uncleaned Packagings:**

### **Recommendations:**

Place in a sealed container and label as waste. Place in a safe area, and comply with all federal, state, provincial and local regulations for disposal.

### Section 14 - TRANSPORT INFORMATION

UN-Number	
DOT, TDG, ADN, IMDG, IATA	Not Regulated
UN proper shipping name	
DOT, TDG, ADN, IMDG, IATA	Not Regulated
Transport hazard class(es)	
DOT, TDG, ADN, IMDG, IATA	
Class	Not Regulated
Packing group	
DOT, TDG, IMDG, IATA	Not Regulated
Environmental hazards:	
Marine pollutant:	No
Special precautions for user:	Not applicable
Transport in bulk according to Annex II of	
MARPOL73/78 and the IBC Code:	Not applicable.
US "Model Regulation":	-

# Section 15 - REGULATORY INFORMATION

# Safety, health and environmental regulations/legislation specific for the substance or mixture Sara

#### Section 355 (extremely hazardous substances)

None of the ingredients is listed.

#### Section 313 (Specific toxic chemical listings)

9016-87-9 Diphenylmethanediisocyanate, isomeres and homologues

101-68-8 4,4'-methylenediphenyl diisocyanate

### TSCA (Toxic Substance Control Act):

All ingredients are listed.



#### Material Name: LiquiSeal Metal Primer (B)

Product #: 330890B

#### **Proposition 65**

Chemicals known to cause cancer:

None of the ingredients is listed.

Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

#### Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

#### **Carcinogenic Categories**

EPA (Environmental Protection Agency):		
9016-87-9	Diphenylmethanediisocyanate, isomeres and homologues	CBD
101-68-8	4,4'-methylenediphenyl diisocyanate	D, CBD
TLV (Threshold Limit Value established by ACGIH):		
None of the ingredients is listed.		
NIOSH-Ca (National Institute for Occupational Safety and Health)		
None of the ingredients is listed.		

#### **Canadian Substance Listings**

Canadian Domestic Substances List (DSL)		
All ingredie	All ingredients are listed.	
Canadian Ingredient Disclosure List (Limit 0.1%):		
101-68-8	4,4'-methylenediphenyl diisocyanate	
Canadian Ingredient Disclosure List (Limit 1%)		
None of the ingredients is listed.		

#### **GHS** label elements

The product is classified and labeled according to the Globally Harmonized System (GHS)

#### Hazard Pictograms





#### Material Name: LiquiSeal Metal Primer (B)

Product #: 330890B

Signal Word: Danger

#### Hazard-determining Components of Labeling:

diphenylmethanediisocyanate, isomeres and homologues 4,4'-methylenediphenyl diisocyanate o-(p-isocyanatobenzyl)phenyl isocyanate

#### **Hazard Statements:**

Harmful if inhaled. Causes skin and eye irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction. May cause respiratory irritation.

#### **Precautionary Statements:**

In case of inadequate ventilation wear respiratory protection. Avoid breathing dust/fume/gas/mist/vapours/spray. Wear protective gloves/protective clothing/eye protection/face protection. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing should not be allowed out of the workplace. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Specific treatment (see on this label). IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If skin irritation occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. IF ON SKIN: Wash with plenty of soap and water. IF INHALED: Call a POISON CENTER/doctor if you feel unwell. If experiencing respiratory symptoms: Call a POISON CENTER/doctor. Take off contaminated clothing and wash it before reuse. Store in a well-ventilated place. Keep container tightly closed. Dispose of contents/container in accordance with local/regional/national/international regulations.

### Section 16 - OTHER INFORMATION

This MSDS format meets ANSI Z400.1-1998, OSHA 1910.1200 and WHMIS requirements. Kemper System America, Inc. provides the information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. This document is intended only as a guide to the appropriate precautionary handling of the material by a properly trained person using this product. Product use and conditions of use are beyond the control of Kemper System America, Inc. Warranty of materials is limited to test results of product performance as detailed in certificates of compliance. Interpretation of test



#### Material Name: LiquiSeal Metal Primer (B)

Product #: 330890B

results is the responsibility of end-user. No other warranties, expressed or implied, are made. Kemper System America, Inc is an ISO 9001:2008 and ISO 14001:2004 registered company.

**Date of preparation / last revision:** 10/24/2014 / 4

#### Key / Legend

ACGIH - American Conference of Governmental Industrial Hygienists; ADR - European Road Transport; AU - Australia; BOD - Biochemical Oxygen Demand; C - Celsius; CA - Canada; CAS - Chemical Abstracts Service; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CLP - Classification, Labelling, and Packaging; CN - China; CPR - Controlled Products Regulations; DFG - Deutsche Forschungsgemeinschaft; DOT - Department of Transportation; DSD -Dangerous Substance Directive; DSL - Domestic Substances List; EEC - European Economic Community; EINECS - European Inventory of Existing Commercial Chemical Substances; EPA -Environmental Protection Agency; EU - European Union; F - Fahrenheit; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; ICAO - International Civil Aviation Organization; IDL - Ingredient Disclosure List; IDLH - Immediately Dangerous to Life and Health; IMDG - International Maritime Dangerous Goods; JP - Japan; Kow - Octanol/water partition coefficient; KR - Korea; LEL - Lower Explosive Limit; LLV - Level Limit Value; LOLI - List Of LIsts™ - ChemADVISOR's Regulatory Database; MAK - Maximum Concentration Value in the Workplace; MEL - Maximum Exposure Limits; NFPA - National Fire Protection Agency; NIOSH - National Institute for Occupational Safety and Health; NJTSR - New Jersey Trade Secret Registry; NTP - National Toxicology Program; NZ - New Zealand; OSHA - Occupational Safety and Health Administration; PH -Philippines; RCRA - Resource Conservation and Recovery Act; REACH- Registration, Evaluation, Authorisation, and restriction of Chemicals; RID - European Rail Transport; SARA - Superfund Amendments and Reauthorization Act; STEL - Short-term Exposure Limit; TDG - Transportation of Dangerous Goods; TSCA - Toxic Substances Control Act; TWA - Time Weighted Average; UEL - Upper Explosive Limit; US - United States.

#### **Other Information**

#### **Disclaimer:**

The information contained herein is based upon data and information available to us, and reflects our best professional judgment. This product may be formulated in part with components purchased from other companies. No warranty of merchantability, fitness for any use, or any other warranty is expressed or implied regarding the accuracy of such data or information. The results to be obtained from the use thereof, or that any such use does not infringe any patent, since the information contained herein may be applied under conditions of use beyond our control and with which we may be unfamiliar, we do not assume responsibility for the results of such application. This information is furnished upon the condition that the person receiving it shall make his own determination of the suitability of the material for his particular use.