

Material Name: Universal Single-Ply Sealant

Product #: 310131

Section 1 - PRODUCT AND COMPANY IDENTIFICATION

Material Name: Universal Single-Ply Sealant Synonyms: Silyl Terminated Polyether Chemical Family: Mixture Product Use: Sealant Restrictions on Use: For industrial use only.

Manufacturer Information

Weatherbond P.O. Box 215 Plainfield, PA 17081 USA Phone: +1-866-471-5125 Emergency Phone #: +1-800-424-9300 (Chemtrec)

Section 2 - HAZARDS IDENTIFICATION

Classification in accordance with paragraph (d) of 29 CFR 1910.1200. Hazardous classification: Irritant Category 2

GHS Label Elements

Symbol(s)



Signal Word: Warning

Hazard Statement(s)

H315 Causes skin irritation H317 May cause allergic skin reaction H318 Causes serious eye damage

Precautionary Statement(s)

P273 Avoid release into the environment
P280 Wear protective gloves/protective clothing/eye protection
P302+P352 IF ON SKIN: Wash with plenty of soap and water.
P305 + P351 IF IN EYES: Rinse cautiously with water for several minutes.
P338 Remove contact lenses, if present and easy to do. Continue rinsing.
P501 Dispose of contents/container in accordance with local regulation.



Material Name: Universal Single-Ply Sealant

Product #: 310131

R-Phrases

R38 Irritating to skin.
R41 Risk serious damage to eyes.
R43 May cause sensitization by skin contact.
S-Phrases
S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
S39 Wear eye/face protection.
Carcinogenity: This product contains no ingredient listed as a carcinogen on California Proposition 65 list.

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

CAS	Component Name	Percent 1-3	
1760-24-3	Amino Silane		

Section 4 - FIRST AID MEASURES

Inhalation

An unlikely route of entry. Remove to fresh air. Consult a physician.

Skin

Clean product from affected area with Ethyl alcohol, then wash with soap and water.

Eyes

Flush with large amounts of water for at least 15 minutes. Consult a Physician if ill effects or irritation occurs.

Ingestion

An unlikely route of entry. Consult a physician.

Section 5 - FIRE FIGHTING MEASURES

Extinguishing Media

Water, CO2, Dry Chemical, Foam.

Unusual Fire and Explosion Hazards: None

Flashpoint: N/A.

Upper Falmmability Limit: N/A

Lower Flammability Limit: N/A



Material Name: Universal Single-Ply Sealant

Product #: 310131

Auto Ignition Temperature: N/A

Sensitivity to Impact: N/A

Sensitivity to Static Discharge: N/A

Hazardous Combustion Products: Thermal decomposition may produce toxic fumes of Carbon Monoxide, Carbon dioxide, Sulfur oxides and Hydrogen sulfide.

Section 6 - ACCIDENTAL RELEASE MEASURES

Handling Precautions: Wear personal protective clothing and equipment, see Section 8. Avoid eye, skin and clothing contact.

Cleanup: Collect spill with absorbent material such as cardboard, allow to cure and place into a container approved for waste disposal.

Regulatory Requirements: Follow applicable OSHA regulations (29 CFR 1910.120).

Section 7 - HANDLING AND STORAGE

Handling Precautions: Use personal protection recommended in section 8. Avoid eye, skin and clothing contact.

Prevention of Fires and Explosions: Product is not considered flammable under normal conditions, and product is not considered explosive.

Storage Requirments: Store in a cool dry area (this product polymerizes when in contact with moisture.)

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Eye/face protection: Wear safety glasses or goggles to avoid eye contact.

Skin Protection: Wear appropriate work clothing. Wear protective shoes. Recommended material: protective skin cream.

Environmental Exposure Control: No specific controls are needed.

Hand Protection: Wear impervious gloves such as vinyl to minimize contact with skin.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

Appearance Paste, scent	mild mint Physical State	Water Solubility: Insoluble
-------------------------	--------------------------	-----------------------------



Material Name: Universal Single-Ply Sealant

Product #: 310131

Odor Threshold	N/A	pH	N/A
Melting Point	N/A	Flash Point	N/A
Freezing point	N/A	Flash Point Method	Based on FP of the most volatile component
Autoignition	N/A	Vapor Pressure	<1
Lower Explosive Limit	N/A	Specific Gravity (water=1)	0.97
Upper Explosive Limit	N/A	% Volatile	2.23%
Vapor Density (air=1)	>1	VOC	21.64 g/l
Density	8.1 lbs./gal. (calculated)		

Other Information

No additional information available.

Section 10 - STABILITY AND REACTIVITY

Chemical Stability

Stable under normal conditions of use.

Conditions to Avoid

None Known

Incompatible Materials None Known

Hazardous decomposition products

Thermal decomposition may produce toxic fumes of Carbon Monoxide (CO) and/or Carbon Dioxide (CO2).

Section 11 - TOXICOLOGICAL INFORMATION

Amino Silane (Refer to sections 2 and 3)

Oral: LD50 > 2,000 mg/kg. Remark: Very low order of toxicity. Skin Absorption: LD50 > 2,000 mg/kg. Remark: Very low order of toxicity. Inhalation: LC50 Not acutely Toxic.

Skin Direct Contact: Slight irritation

Eye Direct Contact: Severe irritation. Remark: Causes corneal injury.

Exposure Limits: Not applicable



Material Name: Universal Single-Ply Sealant

Product #: 310131

Sensitization: No Reproductive Toxicity: No Mutagenicity: No Teratogenicity: No

Synergistic Products: None

Section 12 - ECOLOGICAL INFORMATION

No known applicable information.

Section 13 - DISPOSAL CONSIDERATIONS

If this product as supplied becomes a waste, it does not meet the criteria of a hazardous waste as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. This product becomes a firm synthetic rubber when cured. Please allow to cure before disposal.

Section 14 - TRANSPORT INFORMATION

Special shipping information: None

DOT:Not regulated**TDG:**Not available**PIN:**Not available

Section 15 - REGULATORY INFORMATION

Rotterdam Convention (PIC) Annex III: listed (Tributyl tin compounds (impurities) <2ppm)

U.S. Regulatory information

OSHA 29 CFR 1910-1200 - Irritant.

TSCA – All components of this product are listed on TSCA Inventory.

CERCLA Reportable Quantity – Not applicable.

SARA Title III:

Section 302 Extremely Hazardous Substances – None.



Material Name: Universal Single-Ply Sealant

Section 304 – Not applicable.

Section 311/312 – Immediate (acute) health hazard.

Section 313 – None.

RCRA – Refer to section 13.

California Proposition 65 Carcinogens: This product does not contain any chemicals known by the State of California to cause cancer.

California Proposition 65 Reproductive Toxins: This product does not contain any chemicals known by the State of California to cause reproductive harm.

Canadian WHMIS Classification- D2B

Section 16 - OTHER INFORMATION

HMIG Rating

Health: 1 Fire: 0 Reactivity: 0 Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe * = Chronic hazard

Summary of Changes

New SDS: April 14, 2015

Key / Legend

ACGIH - American Conference of Governmental Industrial Hygienists; ADR - European Road Transport; AU - Australia; BOD - Biochemical Oxygen Demand; C - Celsius; CA - Canada; CAS - Chemical Abstracts Service; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CLP - Classification, Labelling, and Packaging; CN - China; CPR - Controlled Products Regulations; DFG - Deutsche Forschungsgemeinschaft; DOT - Department of Transportation; DSD -Dangerous Substance Directive; DSL - Domestic Substances List; EEC - European Economic Community; EINECS - European Inventory of Existing Commercial Chemical Substances; EPA -Environmental Protection Agency; EU - European Union; F - Fahrenheit; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; ICAO - International Civil Aviation Organization; IDL - Ingredient Disclosure List; IDLH - Immediately Dangerous to Life and Health; IMDG - International Maritime Dangerous Goods; JP - Japan; Kow - Octanol/water partition coefficient; KR - Korea; LEL - Lower Explosive Limit; LLV - Level Limit Value; LOLI - List Of LIsts™ - ChemADVISOR's Regulatory Database; MAK - Maximum Concentration Value in the Workplace; MEL - Maximum Exposure Limits; NFPA - National Fire Protection Agency; NIOSH - National Institute for Occupational Safety and Health; NJTSR - New Jersey Trade Secret Registry; NTP - National Toxicology Program; NZ - New Zealand; OSHA - Occupational Safety and Health Administration; PH -Philippines; RCRA - Resource Conservation and Recovery Act; REACH- Registration, Evaluation, Authorisation, and restriction of Chemicals; RID - European Rail Transport; SARA - Superfund Amendments and Reauthorization Act; STEL - Short-term Exposure Limit; TDG - Transportation of Dangerous Goods; TSCA - Toxic Substances Control Act; TWA - Time Weighted Average; UEL - Upper Explosive Limit; US - United States.

Product #: 310131



Material Name: Universal Single-Ply Sealant

Other Information

Disclaimer:

The information contained herein is based upon data and information available to us, and reflects our best professional judgment. This product may be formulated in part with components purchased from other companies. No warranty of merchantability, fitness for any use, or any other warranty is expressed or implied regarding the accuracy of such data or information. The results to be obtained from the use thereof, or that any such use does not infringe any patent, since the information contained herein may be applied under conditions of use beyond our control and with which we may be unfamiliar, we do not assume responsibility for the results of such application. This information is furnished upon the condition that the person receiving it shall make his own determination of the suitability of the material for his particular use.

Product #: 310131