

WeatherBond

CAV-PRIME Low-VOC Hose & Gun Cleaner



Overview

WeatherBond's CAV-PRIME Low-VOC Hose & Gun Cleaner is designed to clean the spray guns and hoses used to apply CAV-PRIME primers. It can also be used to remove primer from various surfaces including single-ply membranes, accessories, and metal. CAV-PRIME Low-VOC Hose & Gun Cleaner is VOC compliant in all 50 states.

Features and Benefits

- Clears clogged spray guns and hoses
- Can be used to clean spray gun tips
- Allows for easy cleanup of excess primer
- Low-VOC

Coverage Rate

250 – 300 ft² per cylinder

Application

To Clear Clogged Spray Gun and Hose:

Lock spray gun trigger. Attach gun and hose to cylinder. Open valve. Allow line to charge. Let system sit. Aim gun away from people, unlock trigger, and spray until clean. Repeat until system is clear.

To Clean Hose and Gun for Storage:

Turn off the valve on the CAV-PRIME cylinder and depressurize the hose & gun. Lock the spray gun trigger, remove the hose from the CAV-PRIME cylinder, and attach to the cleaner cylinder. Open valve, unlock trigger, and aim gun away from people. Trigger gun into a trash bag or vessel for 10-15 seconds, or until spray is completely clear. Turn off valve on cleaner and depressurize the hose and gun before removing for storage.

To Clean Up Excess Primer:

Spray directly on primer to be removed and wipe with cloth. Can also spray on cloth and wipe. Wear protective, solvent resistant gloves and goggles when cleaning.

Precautions

1. Flammable liquid. Keep away from heat, hot surfaces, sparks, open flames and other ignitions sources. Do not spray on or near an open flame or other ignition source.
2. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment/spray system, personnel, and substrate should be grounded.
3. Use explosion-proof electrical equipment and use only non-sparking tools.
4. Do not pierce or burn, even after use.
5. Use and clean equipment only outdoors or in a well-ventilated area.
6. Stop operation immediately if static sparking occurs. Do not use equipment until you identify and correct the problem.
7. Keep a working fire extinguisher in the work area.
8. Use with adequate ventilation. Avoid inhalation of spray mist and vapors. Harmful or fatal if swallowed. May cause eye irritation. Keep out of reach of children. Use of goggles and gloves recommended. Cylinders are not refillable and when empty are harmless and disposable. Dispose of according to local codes and laws. Keep cans and cylinders below 100°F (37°C).

Typical Properties and Characteristics

Color	Clear
Consistency	Aerosol Spray
VOC	0 g/L
Application Temperature	50°F to 100°F (10°C to 37°C)
Part Number	341407

Typical properties and characteristics are based on samples tested and are not guaranteed for all samples of this product. This data and information is intended as a guide and does not reflect the specification range for any particular property of this product.



WEATHERBOND
ROOFING SYSTEMS

Single-Ply Simplified

P.O. Box 251 | Plainfield, PA 17081 | 866.471.5125 | FAX: 717.960.4034 | www.weatherbondroofing.com

© 2021 WeatherBond. 03.29.21 WB-13651 - "CAV-PRIME Low-Voc Gun & Hose Cleaner Technical Data Bulletin"
WeatherBond is a trademark of WeatherBond.