

WeatherBond

Plastic Locking Insulation Plates



Overview

WeatherBond Roofing Systems' Plastic Locking Insulation Plates are Factory Mutual approved. WeatherBond's 2" (50 mm) HPW Polymer plates should be used for EPDM lap seam fastening. WeatherBond's 3" (75 mm) plates should be used when fastening insulation. All WeatherBond plates are round and designed to be used with WeatherBond fasteners.

Application

- 2" (50 mm) HPW Polymer Plate: Attaches EPDM with Peel & Stick Seam Tape single-ply membrane to the substrate in a mechanically-attached roofing system. Uses WeatherBond #14 HPW fasteners.
- 3" (75 mm) Locking Plastic Plate: Attaches insulation to the substrate. Uses WeatherBond #12 Standard Insulation Fastener or WeatherBond #14 HPW fastener.

Approvals

Check with roofing system manufacturer for FM approvals.

Factory Mutual listings refer to these products as: WeatherBond Plastic Insulation Plate 3" and 2" Barbed Plastic Seam Plate.



Typical Properties and Characteristics

Product	Size* in (mm)	Material	Pkg Quantity	Weight Lbs (KG)
2" HPW Polymer Plate	2 (50)	Nylon	1000	18 (8.17)
3" Locking Plastic Plate	3 (75)	Polypropylene	1000	25 (11.35)

* All sizes are nominal.

Typical properties and characteristics are based on samples tested and are not guaranteed for all samples of this product. This data and information is intended as a guide and does not reflect the specification range for any particular property of this product.