

# WeatherBond

## X-Tenda Coat™ Asphaltic BB Primer

### Overview

X-Tenda Coat Asphaltic BB Primer is a one-component, water-based elastomeric base coating and sealer that is highly resistant to disbonding and prohibits the passage of asphaltic oils from existing asphalt roof materials.

### Features and Benefits

- Excellent stain-blocking performance for silicone roof surface coatings
- Good performance in conditions with ponding water
- Superior in-service flexibility at low temperatures
- Solvent-free and VOC-compliant in all jurisdictions
- Easy application with roller, brush, or commercial spray equipment

### Application

Existing roof membrane, insulation, and all substrates must be sound, dry, clean, and free of oil, grease, dirt, excess mortar, frost, laitance, loose and flaking particles, or other contaminants. All leaks must be sealed prior to application of coating. **DO NOT APPLY IF RAIN OR TEMPERATURES BELOW 50°F (10°C) ARE EXPECTED WITHIN 12 HOURS.** Low temperatures and/or high humidity may require longer drying time.

REVIEW CURRENT WEATHERBOND APPLICATION INSTRUCTIONS FOR SPECIFIC INSTALLATION REQUIREMENTS.

### Ratings and Approvals

- FM Certified
- Florida Approved
- UL Certified

### Typical Properties and Characteristics

Physical Property	Test Method	Typical
Appearance	—	Gray, fluid
Elongation, Initial	ASTM D2370	> 250%
Flash Point	—	Non-flammable
Solids Content by Volume	ASTM D2697	> 48%
Tensile Strength, Initial	ASTM D2370	> 150 psi
Viscosity (Brookfield)	ASTM D2196	21,000 – 28,000 cPs
VOC Content (Maximum)	EPA Method 24	50 g/l
Weight per Gallon	ASTM D1475	10.5 – 11.4 lbs.

Typical properties and characteristics are based on samples tested and are not guaranteed for all samples of this product. This data and information is intended as a guide and does not reflect the specification range for any particular property of this product.

### Storage

Do not store at high temperatures or in direct sunlight. Protect all materials from freezing during transit, handling, storage, and installation.



**WEATHERBOND**  
ROOFING SYSTEMS

Single-Ply Simplified

1285 Ritner Highway | Carlisle, PA 17013 | 866.471.5125 | FAX: 717.960.4034 | [www.weatherbondroofing.com](http://www.weatherbondroofing.com)

© 2024 WeatherBond. 05.24.24 WB-17329 - "X-Tenda Coat Asphaltic BB Primer Technical Data Bulletin"  
WeatherBond is a trademark of WeatherBond. X-Tenda Coat is a trademark of Carlisle Construction Materials, LLC.