

# WeatherBond

## Flexible DASH DC Tools



### Overview

Flexible DASH DC guns are the ideal portable solutions for insulation attachment. Flexible DASH DC simplifies the contractor's life when roofing access is a challenge. Flexible DASH DC gives the contractor a competitive edge over modified systems on small metropolitan and cut-up projects. Manual, pneumatic and battery operated dual cartridge caulk guns are used to apply the Flexible DASH DC adhesive. These tools are available through WeatherBond.

### Pneumatic Dual Cartridge Caulk Gun

Part number: 310680

Included with the pneumatic gun:

- 750 x 750 ml dual cartridge carriage
- Appropriate fittings
- Shoulder strap for operating comfort

### Features and Benefits

- Fast application; install a square of membrane or insulation in less than a minute
- Operating range 50 – 100 psi
- Can be operated with a minimum 100 psi pancake air compressor
- Forward and reverse air buttons
- Pressure regulator to adjust air pressure
- 50–60 lbs of pressure will give you optimum coverage rate

### Operation

- Wear safety glasses and other personal protection equipment to avoid skin contact. See SDS for complete information
- Simply attach air supply (male ¼" NPT thread fitting)
- Insert dual cartridge adhesive into the carriage
- Once the pneumatic gun is loaded and air supply connections are complete, simply squeeze the trigger located on the handle
- To stop, release pressure from the trigger
- To retract the plungers, simply "push in" the air release button located on the side of the handle
- Read and understand its operation. Compressed air can be dangerous when used incorrectly
- Disconnect air supply before maintenance
- Keep plunger clean of urethane adhesive
- Caution – Avoid pressure build-up caused by continuing to engage the trigger when you have a foamed static mixing nozzle. If nozzle is foamed retract the plungers to relieve excess pressure and install a new static mixing nozzle



**WEATHERBOND**  
ROOFING SYSTEMS

Single-Ply Simplified



## Battery Operated Dual Cartridge Caulk Gun

Part number: 310682

Included with the battery operated caulk gun:

- Utilizes a 14.4 volt battery – 1.7 amp-hour
- 1-hour universal charger – 120 vac
- 750 x 750 ml dual cartridge carriage
- A manual hand gun

### Features and Benefits

- Ergonomic design reduces trigger hand fatigue and wrist strain
- Heavy duty all metal gear box develops 620 lbs of force
- Maximum speed of 23 inches per minute
- Dispensing control with the adjustable speed dial
- Auto reverse relieves pressure and reduces cartridge run-on
- Power Efficient – Dispense approximately 30 dual cartridges per charge

### Operation

- Wear safety glasses and other protective equipment to avoid skin contact. See SDS for complete information
- Fully charge the 14.4 volt batteries
- Retract plungers by holding down the top trigger and pulling back on the plunger rod
- Insert dual cartridge into the carriage
- Read and understand its operation
- Squeeze the trigger to dispense adhesive
- Keep plungers clean of urethane adhesive
- Caution - Avoid pressure build-up caused by continuing to engage the trigger when you have a foamed static mixing nozzle. If nozzle is foamed retract the plungers to relieve excess pressure and install a new static mixing nozzle



**WEATHERBOND**  
ROOFING SYSTEMS

Single-Ply Simplified



## Flexible DASH DC Spray System

Part number:

316524-Spray Adapter

316525-Spray Nozzles

A quick and easy attachment for the Pneumatic Dual Cartridge Caulk Gun that allows the contractor to spray full coverage when the job calls for it.

Spray Kit includes:

- Manifold - The manifold includes an air regulator to adjust airflow, vinyl hose and coupler to attach to the nozzle.
- Nozzles (sold separately) – nozzles come packaged 20 per ctn. Each nozzle has the nut to attach to the nozzle to the dual cartridge and the spray tip.

Simply attach the manifold to the spray tip and attach your air supply. Air flow can be adjusted on the manifold to reach optimum coverage (300 sq. ft per ctn).