

WeatherBond

SecurFast™ Insulation Fastening Plate



Overview

WeatherBond's SecurFast Insulation Fastening Plate is specifically designed for coverboard securement under EPDM, PVC, or TPO Roofing Systems. Intended for use in fully adhered single-ply roof systems, SecurFast Plates are stamped from Galvalume®-coated steel for long-term protection against corrosion.

Installation

1. Position plates per WeatherBond Specifications.
2. Secure plates using the appropriate WeatherBond fastener.

REVIEW CURRENT WEATHERBOND INSTALLATION INSTRUCTIONS FOR SPECIFIC INSTALLATION REQUIREMENTS.

Precautions

Eye protection is recommended during drilling and installation of fasteners.

Typical Properties and Characteristics

Property	Results
Size	27/8 Hex
Weight/Carton	38 lbs
Quantity	1,000/Carton
Material	AZ50 Galvalume
Thickness	.019"
Corrosion Resistance	Galvalume-Coated Steel meets the FM 4470 test

Typical properties and characteristics are based on samples tested and are not guaranteed for all samples of this product. This data and information is intended as a guide and does not reflect the specification range for any particular property of this product.



WEATHERBOND
ROOFING SYSTEMS

Single-Ply Simplified

P.O. Box 251 | Plainfield, PA 17081 | 866.471.5125 | FAX: 717.960.4034 | www.weatherbondroofing.com

© 2017 WeatherBond. 08.30.17
WeatherBond is a trademark of WeatherBond. SecurFast is a trademark of Carlisle Construction Materials, LLC.
Galvalume is a trademark of Bethlehem Steel Corp.