

WeatherBond

2" Seam Fastening Plates



Overview

WeatherBond's 2" Seam Fastening Plates are specifically designed for use with Reinforced Perimeter Strip (RPS) or membrane securement for reinforced EPDM. When specified in the current WeatherBond installation instructions, the plates can be used at angle changes with WeatherBond reinforced EPDM, TPO, or PVC membranes.

Features and Benefits

- Compatible with WeatherBond's HPW Fasteners, Purlin Fasteners, and HPWX Fasteners.
- Symmetrical lead distribution.

Installation

1. Position seam plates per WeatherBond specifications.
2. Secure seam plates with the appropriate WeatherBond fastener.

REVIEW CURRENT WEATHERBOND INSTALLATION INSTRUCTIONS FOR SPECIFIC INSTALLATION REQUIREMENTS.

Precautions

Eye protection is recommended during drilling and installation of fasteners.

Typical Properties and Characteristics

Property	Results
Size	2" Diameter (50 mm)
Weight/Carton	22 lbs. (10 kg)
Quantity	1,000/carton
Material	Galvalume® Coated Steel
Thickness	22 Gauge
Pull Through Resistance	500 lb./min. (225 kg/min.)
Corrosion Resistance	Galvalume Coated Steel meets the FM 4470 corrosion test
Compatibility	Accepts WeatherBond's HPW Fasteners, Purlin Fasteners, and HPWX Fasteners

Typical properties and characteristics are based on samples tested and are not guaranteed for all samples of this product. This data and information is intended as a guide and does not reflect the specification range for any particular property of this product.



WEATHERBOND
ROOFING SYSTEMS

Single-Ply Simplified

P.O. Box 251 | Plainfield, PA 17081 | 866.471.5125 | FAX: 717.960.4034 | www.weatherbondroofing.com

© 2021 WeatherBond. 05.21.21 WB-7210 - "Seam Fastening Plates Technical Data Bulletin"
WeatherBond is a trademark of WeatherBond. Galvalume is a trademark of Bethlehem Steel Corp.