

WeatherBond

One- and Two-Way Pressure Relief Breather Vents

Non-Weldable Pressure Relief Breather Vents



Overview

WeatherBond's Non-Weldable One- and Two-Way Pressure Relief Breather Vents are engineered to reduce moisture within the roofing system and release trapped air pressure within the building. One-Way Vents allow trapped air pressure to escape; Two-Way Vents (combined with One-Way Vents) help to reduce moisture.

Features and Benefits

- Made from heavy-gauge spun aluminum for strength and durability
- Conical shape and wide base opening allow for better performance and easier installation than cylindrical vents
- Vandal-proof cap keeps rain and snow out

Installation

1. Consult WeatherBond for project-specific spacing requirements. Cut a 5"-diameter opening through membrane and insulating material, remove membrane and material to vapor barrier or deck, and attach vent to roof deck with appropriate fasteners. Flash in accordance with WeatherBond Specifications and Details.

REVIEW CURRENT WEATHERBOND INSTALLATION INSTRUCTIONS FOR SPECIFIC INSTALLATION REQUIREMENTS.

Typical Properties and Characteristics

Sizes	Height: 8" Base Diameter: 11" Stack Diameter at Base: 5"
Packaging	25/box
Weight	22 lbs.
Material	.051 Aluminum
Product Codes	327975 – One-Way Pressure Relief Vent 327976 – Two-Way Pressure Relief Vent

Typical properties and characteristics are based on samples tested and are not guaranteed for all samples of this product. This data and information is intended as a guide and does not reflect the specification range for any particular property of this product.



WEATHERBOND
ROOFING SYSTEMS

Single-Ply Simplified

Weldable Pressure-Relief Breather Vents



Overview

Available in both TPO and PVC, WeatherBond's Weldable One- and Two-Way Pressure Relief Breather Vents are engineered to reduce moisture within the roofing system and release trapped air pressure within the building. One-Way Vents allow trapped air pressure to escape; Two-Way Vents (combined with One-Way Vents) help to reduce moisture.

Features and Benefits

- Quick and simple installation with no stretching required
- Provides a consistent, finished appearance
- Vandal-proof cap keeps rain and snow out

Installation

1. Consult WeatherBond for project-specific spacing requirements. Cut a 4" diameter opening through membrane and insulating material, remove membrane and material to vapor barrier or deck, and attach vent to roof deck with appropriate fasteners.
2. Heat-weld the base flange to the deck membrane.
3. Once the flashing has completely cooled, check all splices for voids and cold welds. Make any needed repairs.

REVIEW CURRENT WEATHERBOND INSTALLATION INSTRUCTIONS FOR SPECIFIC INSTALLATION REQUIREMENTS.

Typical Properties and Characteristics

Sizes	Height: 5.5" Base Diameter: 14" Stack Diameter at Base: 4"	
Packaging	4/box	
Weight	6.5 lbs.	
Material	Stack Material: Stainless Steel with .060 Weldable Membrane Flange Vent Cap: PVC	
Product Codes	331633 – TPO One-Way Vent 331634 – TPO Two-Way Vent	331635 – PVC One-Way Vent 331636 – PVC Two-Way Vent

Typical properties and characteristics are based on samples tested and are not guaranteed for all samples of this product. This data and information is intended as a guide and does not reflect the specification range for any particular property of this product.