

## Safety Data Sheet

**Material Name: Splice Adhesive**

**Product #: 309550**

---

### Section 1 - PRODUCT AND COMPANY IDENTIFICATION

---

**Material Name:** Splice Adhesive

**Synonyms:** Solvent-Based Adhesive

**Chemical Family:** Adhesive

**Product Use:** Splicing adhesive for EPDM Single-Ply Roofing Membrane

**Restrictions on Use:** For industrial use only.

#### Manufacturer Information

Weatherbond  
P.O. Box 215  
Plainfield, PA 17081  
USA  
Phone: +1-866-471-5125  
Emergency Phone #: +1-800-424-9300 (CHEMTREC)

---

### Section 2 - HAZARDS IDENTIFICATION

---

#### Classification in accordance with paragraph (d) of 29 CFR 1910.1200.

Flammable Liquids - Category 2

Skin Corrosion/Irritation - Category 2

Serious Eye Damage/Eye Irritation - Category 2A

Specific Target Organ Toxicity - Single Exposure - Category 1 ( central nervous system, kidneys, liver, respiratory system )

Specific Target Organ Toxicity - Single Exposure - Category 3

Specific Target Organ Toxicity - Repeated Exposure - Category 1 ( central nervous system, kidneys, respiratory system, Hematopoietic System )

Specific Target Organ Toxicity - Repeated Exposure - Category 2 ( liver, spleen, Cardiovascular system )

#### GHS Label Elements

##### Symbol(s)



##### Signal Word

Danger

##### Hazard Statement(s)

## Safety Data Sheet

**Material Name: Splice Adhesive**

**Product #: 309550**

Highly flammable liquid and vapor  
Causes skin irritation  
Causes serious eye irritation  
Causes damage to organs  
May cause respiratory irritation. May cause drowsiness or dizziness  
Causes damage to organs through prolonged or repeated exposure  
May cause damage to organs through prolonged or repeated exposure

### **Precautionary Statement(s)**

#### **Prevention**

Keep container tightly closed  
Keep away from heat/sparks/open flame/hot surfaces - No smoking  
Ground/Bond container and receiving equipment  
Use explosion-proof electrical/ventilating/lighting equipment  
Take precautionary measures against static discharge  
Use only non-sparking tools  
Use only outdoors or in a well-ventilated area  
Wear protective gloves/protective clothing/eye protection/face protection  
Do not breathe dust/fume/gas/mist/vapours/spray  
Wash thoroughly after handling  
Do not eat, drink or smoke when using this product

#### **Response**

In case of fire: Use appropriate media to extinguish  
If exposed: Call a POISON CENTER or doctor/physician  
IF INHALED: Remove person to fresh air and keep at rest in a position comfortable for breathing  
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower  
If skin irritation occurs: Get medical advice/attention  
Take off contaminated clothing and wash before reuse  
Call a POISON CENTER or doctor if you feel unwell  
Specific treatment (see label)

#### **Storage**

Store in a well-ventilated place. Keep container tightly closed  
Keep cool  
Store locked up

#### **Disposal**

Dispose of contents/container in accordance with local/regional/national/international regulations

---

### **Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS**

---



## Safety Data Sheet

Material Name: Splice Adhesive

Product #: 309550

CAS	Component Name	Percent
Trade Secret	Polyphenol antioxidant	0.1-1
Mixture	Silicon adsorbent mixture	0.5-1.5
108-88-3	Toluene	30-60
1330-20-7	Xylene	7-13
64742-89-8	Solvent naphtha, petroleum, light aliphatic	5-10
67-63-0	Anhydrous isopropanol	5-10
Trade Secret	Tetraisopropyl titanate	1-5
Trade Secret	Phenolic resin	0.1-1
142-82-5	Heptane	5-10

---

### Section 4 - FIRST AID MEASURES

---

#### Description of Necessary Measures

IF exposed or concerned: Get medical advice/attention.

#### Inhalation

IF INHALED: Remove person to fresh air and keep at rest in a position comfortable for breathing. Give artificial respiration if not breathing. Call a POISON CENTER or doctor if you feel unwell.

#### Skin

Remove/Take off immediately all contaminated clothing and wash it before reuse. Rinse skin with water/shower. If skin irritation occurs, get medical advice/attention.

#### Eyes

Rinse cautiously with water for 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists, get medical advice/attention.

#### Ingestion

If swallowed, do not induce vomiting. Immediately call a POISON CENTER or doctor/physician.

#### Indication of any immediate medical attention and special treatment needed

Treat symptomatically and supportively.

#### Most Important Symptoms/Effects

## Safety Data Sheet

**Material Name: Splice Adhesive**

**Product #: 309550**

### **Acute**

Causes skin irritation. Causes serious eye irritation. Causes damage to organs: central nervous system, respiratory system, kidneys, liver. May cause respiratory irritation. May cause drowsiness or dizziness. May cause gastrointestinal irritation.

### **Delayed**

Causes damage to organs through prolonged or repeated exposure: central nervous system, respiratory system, kidneys, Hematopoietic System. May cause damage to organs through prolonged or repeated exposure: liver, spleen, Cardiovascular system.

### **Note to Physicians**

Contains: toluene, xylene, heptane, isopropanol.

---

## Section 5 - FIRE FIGHTING MEASURES

---

### **Extinguishing Media**

#### **Suitable Extinguishing Media**

Dry chemical, foam or carbon dioxide. Water may be ineffective. Use water spray to keep containers cool.

#### **Unsuitable Extinguishing Media**

Do not use high-pressure water streams.

### **Special Hazards Arising from the Chemical**

Highly flammable liquid and vapor. Can burn and explode easily when exposed to open flames or high heat. Vapors are heavier than air and may travel a considerable distance to a source of ignition and flashback.

### **Hazardous Combustion Products**

Oxides of carbon, oxides of nitrogen

### **Fire Fighting Measures**

Wear full protective fire fighting gear including self contained breathing apparatus (SCBA) for protection against possible exposure.

---

## Section 6 - ACCIDENTAL RELEASE MEASURES

---

### **Personal Precautions, Protective Equipment and Emergency Procedures**

Wear personal protective clothing and equipment, see Section 8.

### **Methods and Materials for Containment and Cleaning Up**

Remove all sources of ignition. Avoid breathing vapors. Ventilate affected area. Absorb with earth, sand or other non-combustible material and transfer to container. Use non-sparking tools. Dike for later disposal. Dispose in accordance with all applicable regulations.

### **Environmental Precautions**

Avoid release to the environment.

## Safety Data Sheet

Material Name: Splice Adhesive

Product #: 309550

---

### Section 7 - HANDLING AND STORAGE

---

#### Precautions for Safe Handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not eat, drink or smoke when using this product. Keep away from heat/sparks/open flames/hot surfaces. Take precautionary measures against static discharge. Ground/bond container and receiving equipment. Use non-sparking tools. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. Do not breathe dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid contact during pregnancy/while nursing. **KEEP OUT OF REACH OF CHILDREN.**

#### Conditions for Safe Storage, Including any Incompatibilities

Store in a well-ventilated place. Keep container tightly closed

Keep cool

Store locked up

Keep dry. Keep away from heat and ignition sources. Keep away from incompatible materials. Do not cut, puncture, or weld on or near this container.

#### Incompatible Materials

Strong oxidizing agents, acids, bases

---

### Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

---

#### Component Exposure Limits

<b>Toluene</b>	108-88-3	
ACGIH:	20 ppm TWA	
NIOSH:	100 ppm TWA; 375 mg/m <sup>3</sup> TWA	150 ppm STEL; 560 mg/m <sup>3</sup> STEL
	500 ppm IDLH	
Europe:	50 ppm TWA; 192 mg/m <sup>3</sup> TWA	100 ppm STEL; 384 mg/m <sup>3</sup> STEL
	Possibility of significant uptake through the skin	
OSHA (US):	200 ppm TWA	300 ppm Ceiling
Mexico:	50 ppm TWA LMPE-PPT; 188 mg/m <sup>3</sup> TWA LMPE-PPT	
	Skin - potential for cutaneous absorption	



Safety Data Sheet

Material Name: Splice Adhesive

Product #: 309550

<b>Xylene</b>	1330-20-7	
ACGIH:	100 ppm TWA	150 ppm STEL
Europe:	50 ppm TWA (pure); 221 mg/m <sup>3</sup> TWA (pure)	100 ppm STEL (pure); 442 mg/m <sup>3</sup> STEL (pure)
	Possibility of significant uptake through the skin	
OSHA (US):	100 ppm TWA; 435 mg/m <sup>3</sup> TWA	
Mexico:	100 ppm TWA LMPE-PPT; 435 mg/m <sup>3</sup> TWA LMPE-PPT	150 ppm STEL [LMPE-CT]; 655 mg/m <sup>3</sup> STEL [LMPE-CT]
<b>Anhydrous isopropanol</b>	67-63-0	
ACGIH:	200 ppm TWA	400 ppm STEL
NIOSH:	400 ppm TWA; 980 mg/m <sup>3</sup> TWA	500 ppm STEL; 1225 mg/m <sup>3</sup> STEL
	2000 ppm IDLH (10% LEL)	
OSHA (US):	400 ppm TWA; 980 mg/m <sup>3</sup> TWA	
Mexico:	400 ppm TWA LMPE-PPT; 980 mg/m <sup>3</sup> TWA LMPE-PPT	500 ppm STEL [LMPE-CT]; 1225 mg/m <sup>3</sup> STEL [LMPE-CT]
<b>Magnesium oxide</b>	1309-48-4	
ACGIH:	10 mg/m <sup>3</sup> TWA inhalable fraction	
NIOSH:	750 mg/m <sup>3</sup> IDLH fume	
OSHA (US):	15 mg/m <sup>3</sup> TWA fume, total particulate	
Mexico:	10 mg/m <sup>3</sup> TWA LMPE-PPT as Mg fume	
<b>Heptane</b>	142-82-5	
ACGIH:	400 ppm TWA	500 ppm STEL

## Safety Data Sheet

**Material Name: Splice Adhesive**

**Product #: 309550**

NIOSH:	85 ppm TWA; 350 mg/m <sup>3</sup> TWA	440 ppm Ceiling 15 min; 1800 mg/m <sup>3</sup> Ceiling 15 min
	750 ppm IDLH	
Europe:	500 ppm TWA; 2085 mg/m <sup>3</sup> TWA	
OSHA (US):	500 ppm TWA; 2000 mg/m <sup>3</sup> TWA	
Mexico:	400 ppm TWA LMPE-PPT; 1600 mg/m <sup>3</sup> TWA LMPE-PPT	500 ppm STEL [LMPE-CT]; 2000 mg/m <sup>3</sup> STEL [LMPE-CT]
	Skin - potential for cutaneous absorption	

### Biological limit value

There are no biological limit values for any of this product's components.

### Engineering Controls

Provide local exhaust ventilation system. Ensure compliance with applicable exposure limits.

### Individual Protection Measures, such as Personal Protective Equipment

#### Eye/face protection

Wear splash resistant safety goggles. Provide an emergency eye wash fountain and quick drench shower in the immediate work area.

#### Skin Protection

Wear appropriate work clothing. Wear protective shoes. Recommended material: protective skin cream.

#### Respiratory Protection

A NIOSH approved air-purifying respirator with an appropriate cartridge or canister may be appropriate under certain circumstances where airborne concentrations are expected to exceed exposure limits.

#### Glove Recommendations

Wear appropriate chemical resistant gloves.

---

## Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

---

<b>Appearance</b>	black liquid	<b>Physical State</b>	liquid
<b>Odor</b>	hydrocarbon	<b>Color</b>	black
<b>Odor Threshold</b>	Not available	<b>pH</b>	Not available
<b>Melting Point</b>	-95 to -47 °C (-139 to -53 °F)	<b>Boiling Point</b>	90 - 141 °C (194-286 °F)
<b>Freezing point</b>	Not available	<b>Evaporation Rate</b>	2.3
<b>Boiling Point Range</b>	Not available	<b>Flammability (solid, gas)</b>	Not available



## Safety Data Sheet

Material Name: Splice Adhesive

Product #: 309550

<b>Autoignition</b>	230 °C (475 °F)	<b>Flash Point</b>	-13 °C (8 °F)
<b>Lower Explosive Limit</b>	0.9 %	<b>Decomposition</b>	Not available
<b>Upper Explosive Limit</b>	7 %	<b>Vapor Pressure</b>	21.8 mmHg
<b>Vapor Density (air=1)</b>	3.4	<b>Specific Gravity (water=1)</b>	Not available
<b>Water Solubility</b>	negligible	<b>Partition coefficient: n-octanol/water</b>	Not available
<b>Viscosity</b>	3600 cps	<b>Solubility (Other)</b>	Not available
<b>Density</b>	0.882 (relative)	<b>VOC</b>	605 g/L

### Other Information

No additional information available.

---

## Section 10 - STABILITY AND REACTIVITY

---

### Reactivity

No reactivity hazard is expected.

### Chemical Stability

Stable under normal conditions of use.

### Possibility of Hazardous Reactions

Hazardous polymerization will not occur.

### Conditions to Avoid

Avoid heat, flames, sparks and other sources of ignition. Avoid contact with incompatible materials.

### Incompatible Materials

Strong oxidizing agents, acids, bases

### Hazardous decomposition products

Oxides of carbon, oxides of nitrogen

---

## Section 11 - TOXICOLOGICAL INFORMATION

---

### Information on Likely Routes of Exposure



## Safety Data Sheet

**Material Name: Splice Adhesive**

**Product #: 309550**

**Inhalation**

May cause respiratory irritation. May cause drowsiness or dizziness.

**Skin Contact**

Causes skin irritation.

**Eye Contact**

Causes serious eye irritation.

**Ingestion**

May cause gastrointestinal irritation.

**Acute and Chronic Toxicity**

**Component Analysis - LD50/LC50**

The components of this material have been reviewed in various sources and the following selected endpoints are published:

Polyphenol antioxidant (Trade Secret)

Oral LD50 Rat >200 mg/kg  
Dermal LD50 Rabbit >5010 mg/kg  
Inhalation LC50 Rat >165 mg/L 1 h

Toluene (108-88-3)

Oral LD50 Rat 2600 mg/kg  
Dermal LD50 Rabbit 12000 mg/kg  
Inhalation LC50 Rat 12.5 mg/L 4 h

Xylene (1330-20-7)

Oral LD50 Rat 3500 mg/kg  
Dermal LD50 Rabbit >4350 mg/kg  
Inhalation LC50 Rat 29.08 mg/L 4 h

Solvent naphtha, petroleum, light aliphatic (64742-89-8)

Oral LD50 Mouse 5000 mg/kg  
Dermal LD50 Rabbit 3000 mg/kg

Anhydrous isopropanol (67-63-0)

Oral LD50 Rat 1870 mg/kg  
Dermal LD50 Rabbit 4059 mg/kg  
Inhalation LC50 Rat 72600 mg/m<sup>3</sup> 4 h

Tetraisopropyl titanate (Trade Secret)

Oral LD50 Rat 7460 µL/kg  
Dermal LD50 Rabbit >16 mL/kg

Heptane (142-82-5)

## Safety Data Sheet

**Material Name: Splice Adhesive**

**Product #: 309550**

Oral LD50 Mouse 5000 mg/kg  
 Dermal LD50 Rabbit 3000 mg/kg  
 Inhalation LC50 Rat 103 g/m<sup>3</sup> 4 h

### Immediate Effects

Causes skin irritation. Causes serious eye irritation. Causes damage to organs: central nervous system, respiratory system, kidneys, liver. May cause respiratory irritation. May cause drowsiness or dizziness. May cause gastrointestinal irritation.

### Delayed Effects

Causes damage to organs through prolonged or repeated exposure: central nervous system, respiratory system, kidneys, Hematopoietic System. May cause damage to organs through prolonged or repeated exposure: liver, spleen, Cardiovascular system.

### Irritation/Corrosivity Data

Causes skin irritation. Causes serious eye irritation. May cause respiratory irritation. May cause gastrointestinal irritation.

### Respiratory Sensitization

No data available.

### Dermal Sensitization

It may cause sensitization in some individuals.

### Component Carcinogenicity

<b>Toluene</b>	108-88-3
ACGIH:	A4 - Not Classifiable as a Human Carcinogen
IARC:	Monograph 71 [1999]; Monograph 47 [1989] (Group 3 (not classifiable))
<b>Xylene</b>	1330-20-7
ACGIH:	A4 - Not Classifiable as a Human Carcinogen
IARC:	Monograph 71 [1999]; Monograph 47 [1989] (Group 3 (not classifiable))
<b>Anhydrous isopropanol</b>	67-63-0
ACGIH:	A4 - Not Classifiable as a Human Carcinogen
IARC:	Monograph 71 [1999]; Supplement 7 [1987]; Monograph 15 [1977] (Group 3 (not classifiable))

## Safety Data Sheet

**Material Name: Splice Adhesive**

**Product #: 309550**

<b>Magnesium oxide</b>	1309-48-4
ACGIH:	A4 - Not Classifiable as a Human Carcinogen

**Germ Cell Mutagenicity**

No data available.

**Reproductive Toxicity**

No data available.

**Specific Target Organ Toxicity - Single Exposure**

central nervous system, respiratory system, kidneys, liver

**Specific Target Organ Toxicity - Repeated Exposure**

central nervous system, respiratory system, kidneys, Hematopoietic System, spleen, Cardiovascular system, liver

**Aspiration hazard**

No data available.

**Medical Conditions Aggravated by Exposure**

Aspiration into the lungs may cause chemical pneumonitis.

**Additional Data**

No additional information available.

### Section 12 - ECOLOGICAL INFORMATION

**Ecotoxicity**

Avoid release to the environment.

**Component Analysis - Aquatic Toxicity**

<b>Polyphenol antioxidant</b>	Trade Secret
Fish:	LC50 96 h Oncorhynchus mykiss >0.2 mg/L [semi-static]
Algae:	EC50 72 h Pseudokirchneriella subcapitata >0.2 mg/L IUCLID
Invertebrate:	EC50 48 h Daphnia magna >0.2 mg/L IUCLID
<b>Toluene</b>	108-88-3
Fish:	LC50 96 h Pimephales promelas 15.22 - 19.05 mg/L [flow-through] (1 day old); LC50 96 h Pimephales promelas 12.6 mg/L [static]; LC50 96 h Oncorhynchus mykiss 5.89 - 7.81 mg/L [flow-through]; LC50 96 h Oncorhynchus mykiss 14.1 - 17.16 mg/L [static]; LC50 96 h Oncorhynchus mykiss 5.8 mg/L [semi-static];

## Safety Data Sheet

**Material Name: Splice Adhesive**

**Product #: 309550**

	LC50 96 h <i>Lepomis macrochirus</i> 11 - 15 mg/L [static]; LC50 96 h <i>Oryzias latipes</i> 54 mg/L [static]; LC50 96 h <i>Poecilia reticulata</i> 28.2 mg/L [semi-static]; LC50 96 h <i>Poecilia reticulata</i> 50.87 - 70.34 mg/L [static]
Algae:	EC50 96 h <i>Pseudokirchneriella subcapitata</i> >433 mg/L IUCLID; EC50 72 h <i>Pseudokirchneriella subcapitata</i> 12.5 mg/L [static] EPA
Invertebrate:	EC50 48 h <i>Daphnia magna</i> 5.46 - 9.83 mg/L [static] EPA; EC50 48 h <i>Daphnia magna</i> 11.5 mg/L IUCLID
<b>Xylene</b>	1330-20-7
Fish:	LC50 96 h <i>Pimephales promelas</i> 13.4 mg/L [flow-through]; LC50 96 h <i>Oncorhynchus mykiss</i> 2.661 - 4.093 mg/L [static]; LC50 96 h <i>Oncorhynchus mykiss</i> 13.5 - 17.3 mg/L; LC50 96 h <i>Lepomis macrochirus</i> 13.1 - 16.5 mg/L [flow-through]; LC50 96 h <i>Lepomis macrochirus</i> 19 mg/L; LC50 96 h <i>Lepomis macrochirus</i> 7.711 - 9.591 mg/L [static]; LC50 96 h <i>Pimephales promelas</i> 23.53 - 29.97 mg/L [static]; LC50 96 h <i>Cyprinus carpio</i> 780 mg/L [semi-static]; LC50 96 h <i>Cyprinus carpio</i> >780 mg/L; LC50 96 h <i>Poecilia reticulata</i> 30.26 - 40.75 mg/L [static]
Invertebrate:	EC50 48 h water flea 3.82 mg/L; LC50 48 h <i>Gammarus lacustris</i> 0.6 mg/L
<b>Solvent naphtha, petroleum, light aliphatic</b>	64742-89-8
Algae:	EC50 72 h <i>Pseudokirchneriella subcapitata</i> 4700 mg/L IUCLID
<b>Anhydrous isopropanol</b>	67-63-0
Fish:	LC50 96 h <i>Pimephales promelas</i> 9640 mg/L [flow-through]; LC50 96 h <i>Pimephales promelas</i> 11130 mg/L [static]; LC50 96 h <i>Lepomis macrochirus</i> >1400000 µg/L
Algae:	EC50 96 h <i>Desmodesmus subspicatus</i> >1000 mg/L IUCLID; EC50 72 h <i>Desmodesmus subspicatus</i> >1000 mg/L IUCLID
Invertebrate:	EC50 48 h <i>Daphnia magna</i> 13299 mg/L IUCLID



### Safety Data Sheet

**Material Name: Splice Adhesive**

**Product #: 309550**

<b>Heptane</b>	142-82-5
Fish:	LC50 96 h Cichlid fish 375 mg/L

**Persistence and Degradability**

No information available for the product.

**Bioaccumulative Potential**

No information available for the product.

**Mobility**

No information available for the product.

**Other Toxicity**

No additional information available.

---

**Section 13 - DISPOSAL CONSIDERATIONS**

---

**Disposal Methods**

Dispose of contents/container in accordance with local/regional/national/international regulations.

---

**Section 14 - TRANSPORT INFORMATION**

---

**US DOT Information:**

**Shipping Name:**ADHESIVES

**Hazard Class:** 3

**UN/NA #:** UN1133

**Packing Group:** II

**Required Label(s):** 3

**IATA Information:**

**Shipping Name:**ADHESIVES

**Hazard Class:** 3

**UN#:** UN1133

**Packing Group:** II

**Required Label(s):** 3

**TDG Information:**

**Shipping Name:**ADHESIVES

**Hazard Class:** 3

**UN#:** UN1133

## Safety Data Sheet

**Material Name: Splice Adhesive**

**Product #: 309550**

**Packing Group: II**

**Required Label(s):**

### Section 15 - REGULATORY INFORMATION

**U.S. Federal Regulations**

This material contains one or more of the following chemicals required to be identified under SARA Section 302 (40 CFR 355 Appendix A), SARA Section 313 (40 CFR 372.65), CERCLA (40 CFR 302.4), TSCA 12(b), and/or require an OSHA process safety plan.

Toluene	108-88-3
SARA 313:	1 % de minimis concentration
CERCLA:	1000 lb final RQ; 454 kg final RQ
Xylene	1330-20-7
SARA 313:	1 % de minimis concentration
CERCLA:	100 lb final RQ; 45.4 kg final RQ
Anhydrous isopropanol	67-63-0
SARA 313:	1 % de minimis concentration (only if manufactured by the strong acid process, no supplier notification)

**SARA Section 311/312 (40 CFR 370 Subparts B and C)**

**Acute Health: Yes Chronic Health: Yes Fire: Yes Pressure: No Reactivity: No**

**U.S. State Regulations**

The following components appear on one or more of the following state hazardous substances lists:

Component	CAS	CA	MA	MN	NJ	PA
Toluene	108-88-3	Yes	Yes	Yes	Yes	Yes
Xylene	1330-20-7	Yes	Yes	Yes	Yes	Yes
Anhydrous isopropanol	67-63-0	Yes	Yes	Yes	Yes	Yes
Magnesium oxide	1309-48-4	Yes	Yes	Yes	Yes	Yes
Heptane	142-82-5	Yes	Yes	Yes	Yes	Yes

## Safety Data Sheet

**Material Name: Splice Adhesive**

**Product #: 309550**

**The following statement(s) are provided under the California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65):**

WARNING! This product contains a chemical known to the state of California to cause reproductive/developmental effects

Toluene	108-88-3
Repro/Dev. Tox	developmental toxicity , initial date 1/1/91
	female reproductive toxicity , initial date 8/7/09

**Canadian WHMIS Ingredient Disclosure List (IDL)**

Components of this material have been checked against the Canadian WHMIS Ingredients Disclosure List. The List is composed of chemicals which must be identified on MSDSs if they are included in products which meet WHMIS criteria specified in the Controlled Products Regulations and are present above the threshold limits listed on the IDL

Toluene	108-88-3
	1 %
Anhydrous isopropanol	67-63-0
	1 %
Magnesium oxide	1309-48-4
	1 %
Heptane	142-82-5
	1 %

**Component Analysis - Inventory**

Polyphenol antioxidant (Trade Secret)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	EIN	Yes	Yes	Yes	No	Yes	No	Yes	Yes	No

Toluene (108-88-3)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	EIN	Yes	Yes	Yes	No	Yes	No	Yes	Yes	Yes

Xylene (1330-20-7)



**Safety Data Sheet**

**Material Name: Splice Adhesive**

**Product #: 309550**

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	EIN	Yes	Yes	Yes	No	Yes	No	Yes	Yes	Yes

Solvent naphtha, petroleum, light aliphatic (64742-89-8)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	EIN	Yes	Yes	No	No	Yes	No	Yes	Yes	Yes

Anhydrous isopropanol (67-63-0)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	EIN	Yes	Yes	Yes	Yes	Yes	No	Yes	Yes	Yes

Tetraisopropyl titanate (Trade Secret)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	EIN	Yes	Yes	Yes	No	Yes	No	Yes	Yes	Yes

Magnesium oxide (1309-48-4)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	EIN	Yes	Yes	Yes	No	Yes	No	Yes	Yes	Yes

Heptane (142-82-5)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	EIN	Yes	Yes	Yes	No	Yes	No	Yes	Yes	Yes

**Section 16 - OTHER INFORMATION**

**HMIS Rating**

Health: 2 Fire: 3 Reactivity: 0

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe \* = Chronic hazard



## Safety Data Sheet

**Material Name: Splice Adhesive**

**Product #: 309550**

### **NFPA Ratings**

Health: 2 Fire: 3 Reactivity: 0

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

### **Summary of Changes**

New SDS: March 3, 2015

### **Key / Legend**

ACGIH - American Conference of Governmental Industrial Hygienists; ADR - European Road Transport; AU - Australia; BOD - Biochemical Oxygen Demand; C - Celsius; CA - Canada; CAS - Chemical Abstracts Service; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CLP - Classification, Labelling, and Packaging; CN - China; CPR - Controlled Products Regulations; DFG - Deutsche Forschungsgemeinschaft; DOT - Department of Transportation; DSD - Dangerous Substance Directive; DSL - Domestic Substances List; EEC - European Economic Community; EINECS - European Inventory of Existing Commercial Chemical Substances; EPA - Environmental Protection Agency; EU - European Union; F - Fahrenheit; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; ICAO - International Civil Aviation Organization; IDL - Ingredient Disclosure List; IDLH - Immediately Dangerous to Life and Health; IMDG - International Maritime Dangerous Goods; JP - Japan; Kow - Octanol/water partition coefficient; KR - Korea; LEL - Lower Explosive Limit; LLV - Level Limit Value; LOLI - List Of Lists™ - ChemADVISOR's Regulatory Database; MAK - Maximum Concentration Value in the Workplace; MEL - Maximum Exposure Limits; NFPA - National Fire Protection Agency; NIOSH - National Institute for Occupational Safety and Health; NJTSR - New Jersey Trade Secret Registry; NTP - National Toxicology Program; NZ - New Zealand; OSHA - Occupational Safety and Health Administration; PH - Philippines; RCRA - Resource Conservation and Recovery Act; REACH- Registration, Evaluation, Authorisation, and restriction of Chemicals; RID - European Rail Transport; SARA - Superfund Amendments and Reauthorization Act; STEL - Short-term Exposure Limit; TDG - Transportation of Dangerous Goods; TSCA - Toxic Substances Control Act; TWA - Time Weighted Average; UEL - Upper Explosive Limit; US - United States.

### **Other Information**

#### **Disclaimer:**

The information contained herein is based upon data and information available to us, and reflects our best professional judgment. This product may be formulated in part with components purchased from other companies. No warranty of merchantability, fitness for any use, or any other warranty is expressed or implied regarding the accuracy of such data or information. The results to be obtained from the use thereof, or that any such use does not infringe any patent, since the information contained herein may be applied under conditions of use beyond our control and with which we may be unfamiliar, we do not assume responsibility for the results of such application. This information is furnished upon the condition that the person receiving it shall make his own determination of the suitability of the material for his particular use.