

CAV-GRIP III for use with EPDM
December 7, 2018

To: WeatherBond Roofing Systems' Contractors

WeatherBond Roofing Systems is excited to announce that CAV-GRIP III Low-VOC Adhesive/Primer can now be used to bond WeatherBond EPDM to horizontal substrates for warranty terms up to and including 20-year, 90-mph designs. CAV-GRIP III provides substantial productivity-boosting advantages on the jobsite:

- Can be used in temperatures as low as 25°F (-4°C)
- VOC compliant and very low odor
- Quick application with spray gun
- No stirring and easy clean-up
- Up to 60% labor savings compared to traditional bonding adhesive applications

CAV-GRIP III packaging options and supporting accessories are listed below.

Description	Product Code	Packaging	Weight	Stocking Location(s)	Coverage Rate*
CAV-GRIP III - #40	329902	#40 Cylinder	40 lb	C, G, S, T	1,000 ft ² *
CAV-GRIP III - #85	332659	12 per pallet	85 lb	Direct Ship	2,000 ft ² *
Low-VOC UN-TACK	330793	#8 Cylinder	14 lb	C, T	N/A
Spray Gun w/24" Extension**	330912	Each	2 lb	C, T	N/A
CAV-GRIP 6' Hose	304302	Each	1 lb	C, G, T, S	N/A
CAV-GRIP 12' Hose	304303	Each	2 lb	C, G, T, S	N/A
CAV-GRIP 18' Hose	304304	Each	3 lb	C, G, T	N/A

* Approximate double-sided adhesive application
**Hoses sold separately

CAV-GRIP III has proven to be popular in previously approved applications, including adhering WeatherBond EPDM membranes to vertical surfaces, adhering WeatherBond TPO membranes, and as a primer for VapAir Seal™ 725TR. Contractors who used CAV-GRIP III in the test market have raved about the speed and ease of application, as well as the dramatic reduction in flash-off time. Please give CAV-GRIP III a try on your next adhered project.

If you have any questions, or for more information, please contact your independent sales representative.

Sincerely,



Ronald L. Goodman, EPDM Marketing Manager



WEATHERBOND
ROOFING SYSTEMS

P.O. Box 251 | Plainfield, PA 17081 | 866.471.5125 | FAX: 717.960.4034 | www.weatherbondroofing.com

Single-Ply Simplified