

VapAir Seal™ Flashing Foam #115 Packaging
September 9, 2020

To: WeatherBond Roofing Systems' Contractors

WeatherBond Roofing Systems is pleased to introduce VapAir Seal Flashing Foam #115 packaging. This higher-capacity option provides three times as much coverage as the current VapAir Seal Flashing Foam #41 packaging – 605 board feet compared to 205 board feet, or 9,236 linear feet at 1-inch bead compared to 3,132 linear feet.

Unlike the #41 packaging, the new #115 packaging consists of two cylinders in separate boxes for the A-side and B-side. The VapAir Seal Flashing Foam #115 package comes with the same gun and hose, as well as 10 disposable tips packaged in the A-side box – everything needed for application. If additional tips are needed, Flexible DASH Dual Tank Nozzle Tips (326081) can be purchased through WeatherBond.


VapAir Seal Flashing Foam #115 has the same features and benefits as the #41 packaging:

- Meets ASTM E283 air barrier standards
- Dries tack-free within 30 to 60 seconds
- Can be trimmed within 2 to 5 minutes, fully cured within 1 hour
- Adheres to PVC pipe, wood, brick, block, and steel
- Compatible with VapAir Seal MD, VapAir Seal 725TR, and all of WeatherBond's SureMB products
- Cured foam is resistant to heat and cold (-200°F to 240°F [-129°C to 115°C])

Product Description	Product Code	Weight/ Carton	Stocking Location	Coverage
A-Side	336116	60 lbs.	Direct Ship	605 BF/9,236 LF-1" bead
B-Side	336117	55 lbs.	Direct Ship	605 BF/9,236 LF-1" bead

If you have any questions, please contact your WeatherBond Independent Sales Representative.

Sincerely,



Paul Markel
Manager, Special Applications
WeatherBond Roofing Systems



P.O. Box 251 | Plainfield, PA 17081 | 866.471.5125 | FAX: 717.960.4034 | www.weatherbondroofing.com

Single-Ply Simplified