

**XP HD New Product Announcement
August 20, 2019**

To: WeatherBond Roofing Systems' Contractors

WeatherBond Roofing Systems is pleased to introduce XP HD Polyiso, a ½"-thick insulating cover board for use in mechanically attached and induction welded single-ply membrane roofing systems. XP HD is composed of a high-density closed-cell polyisocyanurate foam core bonded on each side to glass-reinforced felt (GRF) facers. Suitable for re-roofing and new construction applications, XP HD delivers an R-value of 2.5 and a compressive strength of 80 psi.

XP HD – features and benefits:

- ½" high-density insulating cover board
- 80 psi compressive strength
- Glass-reinforced felt (GRF) facers
- Specifically designed for mechanically attached and induction welded single-ply membrane systems
- Lightweight, easy to cut and handle
- Provides a higher R-value than wood fiber and gypsum cover boards
- Environmentally friendly – no CFCs or ozone-depleting components

Product Code	Description	Size	Pallet Qty (pcs/ft ²)	Truckload Qty (ft ²)
334196	0.5 High Density Blk-Blk 48x48 1536sf	4' x 4'	96/1,536	73,728
332958	0.5 High Density Blk-Blk 48x96 1440sf PK	4' x 8'	45/1,440	69,120

If you have any questions, or for more information, please contact your independent sales representative.

Sincerely,



Chad Buhrman
Insulation Product Manager



WEATHERBOND
ROOFING SYSTEMS

P.O. Box 251 | Plainfield, PA 17081 | 866.471.5125 | FAX: 717.960.4034 | www.weatherbondroofing.com

Single-Ply Simplified